

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name: Ethyl Acetate

Additional identification

Chemical name: Ethyl Acetate
CAS-No.: 141-78-6

Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Solvent

Uses advised against: None known

Details of the supplier of the safety data sheet

Manufacturer / Supplier

Shatabdi Chemicals (P) Ltd.
E-16&11, Udyog Kunj Industrial Area,
Near NH-24 Bypass Road,
Ghaziabad, U.P. - 201009

E-mail: contact@shatabdichemicals.com | Ph.: +91-888 88 18 020 / 995 85 95 474

SECTION 2: Hazards identification

Hazard Classification:

Physical Hazards

Flammable liquids Category 2

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Toxicity - Category 3
Single Exposure

OSHA Specified Hazards: Not Applicable

Warning label items including precautionary statement:

Pictogram:



Signal Words: DANGER!

Hazard Statement(s): H225: Highly flammable liquid and vapor.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Precautionary Statement:

Prevention: P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P264: Wash hands thoroughly after handling.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P370 + 378: In case of fire: Use water spray, carbon dioxide, dry chemical or foam for extinction.
P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312: Call a POISON CENTER/doctor if you feel unwell.

Storage: P403+P235: Store in a well-ventilated place. Keep cool.
P233: Keep container tightly closed.
P405: Store locked up.

Disposal: P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

SECTION 3: Composition/information on ingredients

Substances / Mixtures

General information:

Chemical name	Concentration	Additional identification	Notes
Ethyl Acetate	100%	CAS-No.: 141-78-6	#

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

This substance has workplace exposure limit(s).

SECTION 4: First aid measures

Description of first aid measures

Inhalation:	Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention. In case of irritation from airborne exposure, move to fresh air. Get medical attention if symptoms persist.
Skin contact:	Wash with soap and water. Get medical attention if symptoms occur.
Ingestion:	Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Hazards:	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Treatment:	Treat symptomatically.

SECTION 5: Firefighting measures

General Fire Hazards:	Flammable liquid and vapor
------------------------------	----------------------------

Extinguishing media

Suitable extinguishing media:	Water spray; Dry chemical; Carbon Dioxide; Foam
Unsuitable extinguishing media:	None known

Special hazards arising from the substance or mixture:	Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases.
---	--

Advice for firefighters

Special fire fighting procedures:

Water may be ineffective in fighting the fire. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in the case of fire.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear appropriate personal protective equipment.

Environmental Precautions:

Avoid release to the environment.

Methods and material for containment and cleaning up:

Eliminate sources of ignition. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Large Spillages: Use water spray to disperse vapors and dilute spill to a nonflammable mixture. Flush spill area with water spray. Prevent runoff from entering drains, sewers, or streams. Dike for later disposal.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

SECTION 7: Handling and storage:

Precautions for safe handling:

Avoid breathing mist or vapor. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed and in a well-ventilated place.

Specific end use(s):

Solvent

SECTION 8: Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits Country specific exposure limits have not been established or are not applicable unless listed below.

Chemical name	Type	Exposure Limit Values	Source
Ethyl Acetate	TWA	400 ppm	US. ACGIH Threshold Limit Values (01 2010)
	PEL	400 ppm 1400 mg/cu. m.	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Exposure controls

Appropriate engineering controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Eye bath; Washing facilities; Safety shower

Eye/face protection: Wear safety glasses with side shields (or goggles). Wear a full-face respirator, if needed.

Skin protection

Hand Protection: It is a good industrial hygiene practice to minimize skin contact. For operations where prolonged or repeated skin contact may occur, chemical-resistant gloves should be worn. Contact health and safety professional or manufacturer for specific information.

Other: No data available.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices.

Environmental Controls: No data available

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state:	Liquid
Form:	Liquid
Color:	Colorless
Odor:	Sweet, ester
Odor Threshold:	3.9 ppm
pH:	No data available
Freezing Point	-83 °C
Boiling Point:	78 °C
Flash Point:	-4 °C (Tag closed cup)
Evaporation Rate:	4.1
Flammability (solid, gas):	No data available
Flammability Limit - Upper (%)-:	No data available
Flammability Limit - Lower (%)-:	No data available
Vapor pressure:	99 mbar (20 °C)
Vapor density (air=1):	3
Specific Gravity:	0.902 (20 °C)
Solubility(ies)	
Solubility in Water:	Moderate
Solubility (other):	No data available
Partition coefficient (n-octanol/water):	Pow: 5.4 log Pow: 0.73
Autoignition Temperature:	No data available
Decomposition Temperature:	(DSC) No exotherm to 500°C
Dynamic viscosity:	No data available
Kinematic viscosity:	Not determined
Explosive properties:	No data available
Oxidizing properties:	No data available

Other information

Minimum ignition temperature:	485 °C (ASTM D2155)
-------------------------------	---------------------

SECTION 10: Stability and reactivity

Reactivity:	None known
Chemical Stability:	Stable
Possibility of Hazardous Reactions:	None known
Conditions to Avoid:	Heat; sparks; flames
Incompatible Materials:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon Dioxide; Carbon Monoxide

SECTION 11: Disposal considerations

Waste treatment methods

General information: No data available

Disposal methods: Dispose of waste and residues in accordance with local authority requirements. Mix with compatible chemical which is less flammable and incinerate. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.